

StaticSmart™

ESD Quartz System Flooring Maintenance Procedures

Normal Cleaning Procedures

Julie Industries, Inc. StaticSmart™ ESD Polymeric Flooring does not require special maintenance beyond normal cleaning and housekeeping. Normal cleaning procedures include sweeping, mopping, hot water washdown, high pressure (>1500 psi) power washing, and scrubbing machines. Detergents and caustic cleaning solutions suitable for the clean up of the dirt or soil conditions may be used as needed. If you are not sure of the chemical make-up of a particular cleaner, test a small amount on an inconspicuous area of the floor. Typically citrus based cleaners that do not leave a residue are best. *Note: the floor should not be cleaned with any type of cleaner or water 5 to 7 days after installation so the resins can fully cure.

Products and Procedures

Julie Industries, Inc. recommends the use of the following approved cleaning products:

- Rust-Oleum "Industrial Pure Strength™ Cleaner Degreaser #3599",
- S. C. Johnson & Sons "Breakup™", "J-Shop", or equal "Penetone Powercleaner 155".

Use all cleaners in accordance with the manufacturer's instructions. Take all due precautions when using any cleaning product as floor surfaces may become extremely slippery.

As previously stated, all washing (even with plain water) should be avoided for five days after application (>70° F). Contact with water prior to this time may result in surface dulling or color change.

Mechanical floor scrubbers may be used as required. On Julie Industries, Inc. StaticSmart™ ESD Polymeric Flooring, 3M ScotchBrite™ white pads are recommended. Do not use pads more aggressive than green. Test pads in an inconspicuous area of the floor before use.

Some contaminants such as acids and some solvents may discolor the surface of the floor without causing damage to the floor itself. For spot cleaning with solvent, use xylene (xylol) or isopropyl alcohol (IPA). Do not use any solvent in the vicinity of open flame, open lights or spark producing equipment.

Do not use waxes or acrylic floor finishes or dust mop treatments.

Questions/Assistance

Any questions regarding cleaning and maintenance should be referred to JULIE Industries Customer Service at 978-988-8802, Monday-Friday between 8:00 am and 5:00 pm EST.

Julie Industries
StaticSmart™ Solutions
www.julieindustries.com

355 Middlesex Avenue
Wilmington, MA 01887
Tel: 978-988-8802
Fax: 978-988-8803

