

SECTION I - IDENTITY

PRODUCT NAME: UTP Static Control

CHEMICAL NAME: Water Base Adhesive

Product available in **1 gallon (Item 1848)** and **4 gallon (Item 2087)** sizes.

Para-Chem

PO Box 127,
Simpsonville, SC 29681

24-Hour Emergency Phone Number

(864) 967-7691

Date Issued

DECEMBER 4, 2007

Hazardous - NO

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious 4 = Most Hazardous

SECTION II - HAZARDOUS INGREDIENTS AND EXPOSURE LIMITS

Hazardous Components CAS Reg#	PEL	TWA	STEL	Other Limits IDLH	% (opt)
No ingredients requiring reporting					

SECTION III - HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Eyes, skin, inhalation.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: May cause slight to moderate irritation depending upon degree and duration of exposure.

SKIN CONTACT: May cause slight irritation.

INGESTION: May cause stomach discomfort, nausea, vomiting, or diarrhea.

INHALATION: No effects expected.

CHRONIC: None known.

CARCINOGENICITY: This product contains no ingredient above the OSHA minimum reporting threshold listed as a carcinogen by IARC, NTP, or OSHA

SECTION IV - FIRST AID MEASURES

EYE CONTACT: Flush with water for 15 minutes. Contact a physician if irritation occurs.

SKIN CONTACT: Wash with soap and water.

INGESTION: Induce vomiting, contact a physician.

INHALATION: Remove to fresh air.

SECTION V - FIRE-FIGHTING MEASURES

FLASH POINT (o)F: None.

FIRE-FIGHTING INSTRUCTIONS: Use protective clothing and self-contained breathing apparatus.

EXTINGUISHING MEDIA: Water fog, CO2, dry chemical, and chemical foam.

DECOMPOSITION PRODUCTS: Dried material may produce CO, CO2, H2O, NxO, and hydrocarbons.

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spill. Transfer to secure container(s) for recovery or disposal. Dispense sand, sawdust, or vermiculite and absorb residue. Collect and place in waste container. Wash area thoroughly with water.

SECTION VII - HANDLING AND STORAGE

HANDLING: Use good hygienic practices. (Wash hands before eating, using washroom, or smoking.)

Keep out of the reach of children.

STORAGE: Store above 40o F. Freeze-thaw stable up to five cycles at 20o F.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT:

EYE/FACE PROTECTION: Wear safety glasses or splash goggles if contact with material is likely.

SKIN PROTECTION: Wear impervious synthetic rubber gloves where contact with material is likely.

RESPIRATORY PROTECTION: Not normally required with good ventilation.

ENGINEERING CONTROLS: Normal room ventilation. Use site-specific mechanical exhaust where processing conditions or enclosed work areas create accumulation or concentration of fumes.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (oF): 212

SPECIFIC GRAVITY (WATER = 1): 1.0

VAPOR PRESSURE: Same as water.

VAPOR DENSITY (air=1): Same as water.

% VOLATILE BY WEIGHT: 43

pH: 7

APPEARANCE AND ODOR: Gray paste with black\ brown colored fibers and mild odor.

SECTION X - STABILITY AND REACTIVITY

CHEMICAL STABILITY: Stable.

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None known.

HAZARDOUS DECOMPOSITION PRODUCTS: None.

SECTION XI - TOXICOLOGICAL INFORMATION

No information.

SECTION XII - ECOLOGICAL INFORMATION

No information.

SECTION XIII - DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State and Local regulations.



Julie Industries, Inc.
PO Box 153 | North Reading, MA 01864
phone: (978) 276-0820 | fax: (978) 276-0821
www.julieind.com

SECTION XIV - TRANSPORT INFORMATION

For domestic transportation purposes, this product is not designated as a hazardous material by the U.S. Department Of Transportation.

SECTION XV - REGULATORY INFORMATION

TSCA: The components of this product are listed on the TSCA inventory

SARA TITLE III:

Section 311 and 312 Health and physical hazards:

Immediate	Delayed	Fire	Pressure	Reactivity
[]	[]	[]	[]	[]

Section 313: Contains no components at or above EPA reporting thresholds.

CALIFORNIA VOC (Volatile Organic Compound) COMPLIANCE:

Solvent Free Product.

SCAQMD Rule 1168: VOC compliant.

SCAQMD Rule 443.1: Grams of VOC per Liter of Material < 17 grams/liter.

Grams of VOC per Liter of Coating < 28 grams/liter.

SECTION XVI - OTHER INFORMATION

HMIS RATINGS: Health = 1

Flammability = 0

Reactivity = 0

Personal Protective Equipment = B

Hazard rating scale: 0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Severe

Julie Industries, Inc. believes the statements, technical information and recommendations contained herein are reliable. They are given without warranty or guarantee of any kind, expressed or implied.